



SYNERGO II™

Multi Tilt [Industrial vinyl]

STANDARD	BACKREST	
	3" height adjustment «Floating without interval »	
	Backrest adjustment range 22" to 25"	
	Ergonomic padded backrest (20,5"w x 22,5"h)	
	Backrest in 3 sections (optimized lumbar support)	
	SEAT	
	High resilience memory foam	
	Profiled seat (20"w x 17"d x 3"h)	
	MULTI TILT MECHANISM	
	Mechanism type «Floating without interval »	
Floating spring tension adjustment		
Seat height adjustment		
Seat angle adjustment		
Backrest angle adjustment		
2,5" seat depth adjustment		
BASES		
28" industrial steel		
SEAT HEIGHT ADJUSTMENT		
Cylinder 100 mm (18.5" – 22.5")		
CASTERS / GLIDES		
3" rubber casters (slow rolling)		

ADDITIONAL OPTION	Plastic back shell	
	Heavy use version	
	Extra lumbar support	
	Memory foam (seat)	
	Memory foam (backrest)	
	Height adjustment headrest (3")	
	Height adjustment headrest (3"), depth (4.5")	
	32" steel industrial base	
	24" footrest (adjustable height)	
Tool compartement (11"w x 6"d x 1"h)		
Tool compartement (19"w x 8"d x 1"h)		

OPTIONS	BACKREST		
	Small Ergonomic padded backrest (17,5"w x 21"h)		
	ARMREST		
	Standard: height and side adjustment, moves 2" forward and swivels		
	Standard: height and lateral adjustment, moves 2" forward		
	Gel: height, side adjustment and swivels		
	SEAT		
	Seat size options		
	Large format (24"w x 19,5"d x 5"h)		
	Long format (19,5" w x 19"d x 4"h)		
Small format (19"w x 17"d x 3"h)			
BASES			
27" fiberglass reinforced nylon base			
5 double nylon casters 2"			
SEAT HEIGHT ADJUSTMENT			
Cylinder 80 mm (18"-21")			
Cylinder 140 mm (21"-26,5")			
Cylinder 200 mm (23"-31,5")			
Cylinder 270 mm (26,5"-36,5")			
CASTERS / GLIDES			
3" rubber casters with brake (slow rolling)			
3" double rubber casters (fast rolling)			
3" double rubber casters with brake (fast rolling)			
Roulettes de 2" doubles ESD (base en nylon)			
2" glides			
3" glides			