



# TF 190™

## Multi Tilt [Welding]

STANDARD	<b>BACKREST</b>	
	2" height adjustment «Floating without interval »	
	Backrest adjustment range 23" to 25"	
	Ergonomic padded backrest (17,5" w x 21" h)	
	<b>SEAT</b>	
	High resilience Velva foam	
	Profiled seat (20" w x 18.25" d x 2" h)	
	<b>MULTI TILT MECHANISM</b>	
	Mechanism type «Floating without interval »	
	Floating spring tension adjustment	
	Seat height adjustment	
	Seat angle adjustment	
	Backrest angle adjustment	
	2,5" seat depth adjustment	
<b>BASES</b>		
28" industrial steel		
24" footrest (adjustable height)		
<b>SEAT HEIGHT ADJUSTMENT</b>		
Cylinder 200 mm (20"-30")		
<b>CASTERS / GLIDES</b>		
3" rubber casters (slow rolling)		

OPTIONS	<b>BACKREST</b>	
	Medium format (16" w x 17" h)	
	Small format (16" w x 14" h)	
	<b>ARMREST</b>	
	Fireproof height, side adjustment and swivels	
	<b>SEAT</b>	
	Confortable format (20" w x 18,25" d x 3" h)	
	2,5" seat depth adjustment	
	<b>BASES</b>	
	27" fiberglass reinforced nylon base	
	5 double caster 2" nylon	
	<b>SEAT HEIGHT ADJUSTMENT</b>	
	Cylinder 270 mm (25.5"-35,5")	
	<b>CASTERS / GLIDES</b>	
3" rubber casters with brake (slow rolling)		
3" double rubber casters (fast rolling)		
3" double rubber casters with brake (fast rolling)		
2" glides		
3" glides		

ADDITIONAL OPTIONS	Heavy use version
	Extra lumbar support
	Memory foam (seat)
	Memory foam (backrest)
	32" industrial steel base
	Tool compartment (11" w x 6" d x 1" h)
Tool compartment (19" w x 8" d x 1" h)	

